


IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A method of imparting odor to an odorless combustible gas, said method comprising:
 adding to said odorless combustible gas an odorizing composition comprising:
 A. at least one acrylic C₁-C₁₂-alkyl ester,
 B. at least one N compound with a boiling point of from 90 to 210°C and a molecular weight of from 80 to 160 and optionally
 C. an antioxidant,
 wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached, and
 wherein said odorizing composition is sulfur-free.
2. (Previously presented) The method according to Claim 1, wherein at least two different acrylic C₁-C₁₂-alkyl esters A are added.
3. (Previously presented) The method according to Claim 1, wherein a mixture of two different acrylic C₁-C₆-alkyl esters is added as component A.
4. (Cancelled)

5. (Previously presented) The method according to Claim 1, wherein a compound of the formula



is component B, where

R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl; and

wherein component B is chosen from 2-methylpyrazine, 2,3-dimethylpyrazine, 2,6-dimethylpyrazine, 2,3,5-trimethylpyrazine, tetramethylpyrazine, 2-ethylpyrazine, 2,3-diethylpyrazine, 5,2-methylethylpyrazine, 2,3-methylethylpyrazine, 5,2,3-methyldiethylpyrazine, 3,5,2-dimethylethylpyrazine, or 3,6,3- dimethylethylpyrazine.


6. (Previously presented) The method according to Claim 1, wherein component B is used in an amount of from 1 to 100 parts by weight per 1,000 parts by weight of A.
7. (Previously presented) The method according to Claim 1, wherein component C is used in an amount of from 0.01 to 5 parts by weight per 1,000 parts by weight of A.
8. (Cancelled)
9. (Currently amended) A combustible gas comprising:

- 1) an odorless gas; and
- 2) an odorizing composition comprising:
 - A. at least one acrylic C₁-C₁₂-alkyl ester,
 - B. at least one N compound with a boiling point of from 90 to 210°C and a molecular weight of from 80 to 160 and optionally
 - C. an antioxidant,

wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached

wherein said odorizing composition is sulfur-free.


10. (Previously presented) The gas according to Claim 9, wherein at least two different acrylic C₁-C₁₂-alkyl esters are added.
11. (Previously presented) The gas according to Claim 9, wherein a mixture of two different acrylic C₁-C₆-alkyl esters are added as component A.
12. (Cancelled)
13. (Previously presented) The gas according to Claim 9, wherein said at least one N compound is of the formula:



wherein R¹ to R⁴, independently of one another, are

hydrogen or C₁-C₄-alkyl.

14. (Previously presented) The gas according to Claim 9, wherein said at least one N compound is present in an amount of from 1 to 100 parts by weight per 1,000 parts by weight of said Component A.
15. (Previously presented) The gas according to Claim 9, wherein at least said antioxidant is used in an amount of from 0.01 to 5 parts by weight per 1,000 parts by weight of said Component A.
16. (Previously presented) The method according to Claim 1, wherein said odor imparting components that are added to said combustible gas are non-corrosive.
17. (Previously presented) The gas according to Claim 9, wherein said odor imparting components that are added to said combustible gas are non-corrosive.
18. (Previously presented) The gas according to Claim 1, wherein said at least one N compound is of the formula:




(I)

wherein R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl.

19. (Previously presented) A method of odorizing an odorless combustible gas by adding to said odorless combustible gas an odorizing composition comprising:

- A. at least one acrylic C₁-C₁₂-alkyl ester,
- B. at least one N compound of the formula:




wherein R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl, and optionally

- C. an antioxidant,

wherein said odorizing composition is sulfur-free.

20. (Previously presented) The method according to Claim 19, wherein components A and B are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached.

21. (Previously presented) The gas according to Claim 9, wherein said at least one N compound is of the formula:



ATTORNEY DOCKET: 3968.062

wherein R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl, and optionally


C. an antioxidant.

22. (Previously presented) An odorless combustible gas comprising:

- 1) an odorless gas; and
- 2) an odorizing composition comprising:

A. at least one acrylic C₁-C₁₂-alkyl ester,

B. wherein at least one N compound is of the formula:



wherein R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl, and optionally

C. an antioxidant


wherein said odorizing composition is sulfur-free.

23. (Currently amended) The gas according to Claim 22, wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached.

24. (Previously presented) An odorizing agent suitable for

imparting odor to an odorless combustion gas, the odorizing agent comprising:

- A. at least one acrylic C₁-C₄-alkyl acrylate,
- B. at least one compound of the formula:



wherein R¹ to R⁴, independently of one another, are hydrogen or C₁-C₄-alkyl, and optionally

- C. an antioxidant

wherein said odorizing agent is sulfur-free.

25. (Currently amended) A method of imparting odor to an odorless combustible gas, said method comprising:

adding to said odorless combustible gas

- A. a mixture of two acrylic C₁-C₁₂-alkyl esters, wherein the weight ratio of the two acrylic esters is 9:1 to 1:9,
- B. at least one N compound with a boiling point of from 90 to 210°C and a molecular weight of from 80 to 160 and optionally
- C. an antioxidant,

wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached.

26. (Currently amended) A combustible gas comprising:

- 1) an odorless gas; and
- 2) an odorizing composition comprising:

- A. a mixture of two acrylic C₁-C₁₂-alkyl esters, wherein the weight ratio of the two acrylic esters is 9:1 to 1:9,
 - B. at least one N compound with a boiling point of from 90 to 210°C and a molecular weight of from 80 to 160 and optionally
 - C. an antioxidant,
- wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached, and wherein said components A and B are substantially sulfur-free.

27. (New) A method of imparting odor to an odorless combustible gas, said method comprising:

adding to said odorless combustible gas an odorizing composition comprising:

- A. at least one acrylic C₁-C₁₂-alkyl ester,
- B. at least one N compound with a boiling point of from 90 to 210°C and a molecular weight of from 80 to 160 and optionally
- C. an antioxidant,

ATTORNEY DOCKET: 3968.062

wherein components A and B are odorants and are added to said combustible gas in an amount effective to act as a warning signal to warn of presence of said combustible gas in an enclosed space before an ignition limit of said combustible gas in said enclosed space is reached,

wherein said odorizing composition is sulfur-free, and wherein the odor excludes kitchen and home odors.